



A member of **UEM**



Cast
with Innovation and
Sustainability

Build with Confidence.
Build with CIMA.
We are here to support you

Corporate Office

Cement Industries of Malaysia Berhad
197201000294 (11986-T)
Annexe 2, Persada PLUS, Persimpangan Bertingkat Subang
KM 15, Lebuhraya Baru Lembah Klang
47301 Petaling Jaya, Selangor, Malaysia



Contact us on WhatsApp:
+603 8604 6608



SHIM
MS IN 17PM 2014
CERTIFICATION NO : PC0005086



Visit Our Website:
www.cima.com.my

NS
Optimo
Building the Future

ADVANTAGE



Improved Workability

Designed for effortless handling and application



Reduced Bleeding

Minimises water separation in cement mixtures, ensuring optimum consistency



Lower Environmental Impact

Reduces carbon emissions and conserves natural resources



Enhanced Cohesiveness

Delivers a smoother and more consistent mix



Improved Surface Finishing

Produces a high-quality finish



Richer Mix

Provides a denser and more durable cement, ensuring long-lasting results



INTRODUCING MALAYSIA'S FIRST

52.5N GRADE PORTLAND LIMESTONE CEMENT (PLC)

NS OPTIMOCAST CEM II/A-L 52.5N

OFFERS THE SAME OUTSTANDING PERFORMANCE AS OPC,
BUT WITH A SIGNIFICANTLY LOWER CARBON FOOTPRINT.

This innovative product is engineered with the addition of raw limestone, effectively reducing carbon emissions while ensuring that the exceptional quality and durability you expect remains intact.



Reduce Carbon Emissions



Conserve Natural Resources



Align To Global Sustainability Goals



Excellent 52.5N Performance

APPLICATIONS

- Use it everywhere
- Ready-mix concrete
- Pre-cast concrete
- Mortars and grouts
- Soil stabilizations
- Full-depth reclamation
- Concrete masonry units
- Other applications for sustainable building



NS OptimoCast is
available in 50kg bags

MEETS SPECIFICATIONS

PLC has been successfully utilised worldwide for over 50 years, with its performance rigorously validated over the past 2 years in local applications.



TESTED & APPROVED

Fully compliant with industry standards, this product meets both national and international specifications, including MS EN 197-1 CEM II/A-L 52.5N

